

PRODUCT ADVICE

INTERIOR WOOD PRIMER & UNDERCOAT



All Farrow & Ball paints are eco friendly and comply with the latest environmental legislation regarding the VOC (volatile organic compounds) content of paints.

Availability: In 750ml, 2.5 litre and 5 litre tins in ten colours (1, 10, 15, 18, 22, 26, 32, 37, 49 & White). Available direct from Farrow & Ball, our Showrooms and selected stockists internationally.

Usage: A durable primer and undercoat designed for painting internal surfaces only. For brush or spray application to unpainted wood and galvanised surfaces. Provides good adhesion, is easily sanded to give a smooth finish, and enhances the colour of the topcoat.

It is also the recommended primer and undercoat when applying Farrow & Ball Dead Flat onto fully dried plaster.

Preparation: All surfaces must be sound, clean, dry and free from dirt, grease and other contamination. **Flaking or peeling may occur if painting over weak paint layers.**

Fill any cracks, holes and open joints with an interior wood filler.

Surface filling will require more maintenance. Neutralise when caustic strippers have been used.

New wood surfaces – where required use Farrow & Ball Stain Block Primer to patch prime knotty or resinous woods. Follow with a diluted first coat of Farrow & Ball Interior Wood Primer & Undercoat (20% water) and then one full coat. Proceed with two coats of Farrow & Ball Estate[®] Eggshell, Farrow & Ball Dead Flat or Farrow & Ball Full Gloss.

Previously painted wood surfaces - sand back areas of old paint that have peeled or blistered, rub down well to achieve a good 'key' and apply one full coat of Farrow & Ball Interior Wood Primer & Undercoat. Proceed with two coats of Farrow & Ball Estate[®] Eggshell, Farrow & Ball Dead Flat or Farrow & Ball Full Gloss.


Galvanised surfaces – treat with Etch Primer or Mordant Solution taking care to follow manufacturer's instructions and health and safety advice. Clean with a detergent wash when dry. Proceed with two coats of Farrow & Ball Estate[®] Eggshell, Farrow & Ball Dead Flat or Farrow & Ball Full Gloss.

Other ferrous metal surfaces – apply two coats of Farrow & Ball Metal Primer. Proceed with two coats of Farrow & Ball Estate[®] Eggshell, Farrow & Ball Dead Flat or Farrow & Ball Full Gloss.

Painting: Do not paint in temperatures below 10°C or excessive heat above 30°C.

Please check for colour accuracy prior to use as we will not be liable for decorating costs caused as a result of an incorrect colour being applied. When more than one tin of the same colour is to be used ensure that batch numbers are identical or intermix before use.

Disclaimer: The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.



PAS_UK

PRODUCT ADVICE

INTERIOR WOOD PRIMER & UNDERCOAT



Painting cont/... Stir thoroughly before use.

Apply one coat, lightly sand with a fine abrasive paper to give a smooth finish for your top coat.

(Airless Spraying - Good results can be achieved by a set up of 18 thou 65° angle tip using a pressure of between 2400 – 2700 psi).

Clean up: Clean brushes and rollers with warm soapy water.

Cleaning: N/A

Formulation: A water based paint made using a traditional alkyd resin.

Storage: This product is water based and must be protected from frost and extreme temperatures. Use within 6 months of purchase. We accept no responsibility for the deterioration of contents or packaging after this date.

Disposal: Though water based, please do not dispose of into watercourse. Waste materials must be disposed of in accordance with the Environmental Protection Act 1990 and relevant regulations made there under. For further information contact the environment office at your local council.

Health & Safety: Ensure good ventilation during application and drying. Avoid contact with skin and eyes. In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. After contact with skin wash immediately with plenty of soap and water or a proprietary skin cleanser. Keep out of reach of children. **Safety Data Sheets are available for professional users on request.**

Environment: **Actual VOC content g/l** 19.5 g/l

VOC content w/w: 1.41%

Classification: Low

2010 max. permitted limit grams per litre 30 g/l

CATEGORY g

Coverage	Drying Time	Recoat Time	Sheen Level	Thinners
Up to 60 m ² per 5 litres dependant on the surface being painted	Touch dry 1 hour depending on conditions.	Minimum 4 hours depending on conditions. Ensure the surface is completely hard before closing newly painted windows and doors.	N/A	Water if required

Issue 3 January 2010

Disclaimer: The information given in these specification sheets and technical advice - whether verbal, in writing or by way of trials - is for guidance and is given in good faith but without warranty, since skill of application and site conditions are beyond our control. For further information please contact our Customer Services Department. We can accept no liability for the performance of the products arising out of such use, beyond the value of the goods delivered by us. This does not affect your statutory rights.

PAS_UK