

# Beckers



## Golvolja

Beckers Golvolja is a polishable oil for hardwood flooring and furniture.

Beckers Golvolja is a product that is used to oil unfinished hardwood flooring and furniture. The oil can also be used as a primer before floors are treated with Parkettlack varnish to create a darker and deeper tone in the flooring.

Beckers Golvolja can be tinted with oil-based artists' colours (Beckers Normalfärg) if another colour is desired.



### TECHNICAL DATA

|                          |  |
|--------------------------|--|
| <b>BINDER</b>            | Oils.  |
| <b>SOLVENT</b>           | Low aromatic white spirit.   |
| <b>THINNING</b>          | Use low aromatic white spirit.   |
| <b>COVERAGE</b>          | About 5 m <sup>2</sup> /litre depending on the absorbent properties of the wood. |
| <b>TOOLS</b>             | Use a paintbrush, roller or floor varnishing tool.                               |
| <b>CLEANING OF TOOLS</b> | Use Beckers Penseltvätt brush cleaner or white spirit.                           |
| <b>TIME TO RECOAT</b>    | Wait about 24 hours at a temperature of +23°C and 50% humidity.                  |
| <b>DRYING TIME</b>       | About 24 hours at a temperature of +23°C and 50% humidity.                       |
| <b>COLOUR RANGE</b>      | Colourless.  |
| <b>FLAMMABILITY</b>      | Class 2b, flammable.   |

# Golvolja

**Oiling of hardwood flooring:** The wood has to be dry and clean before you oil it. Apply Golvolja flowingly with a paintbrush or roller. While the surface is still wet, use a lint-free rag to wipe away excess oil. The surface can be polished with a floor polisher after about 15 minutes, or by hand with a Scotch Brite pad. If the surface finish is too thin, repeat the treatment procedure described above.

**Maintenance:** Clean oiled hardwood flooring with well a wrung-out rag. Then treat the floor with a thin coat of Golvolja diluted 1:1 with white spirit. Let the floor dry about half an hour, then polish the surface.

Stains that cannot be removed with a well wrung-out scouring cloth can be rubbed with fine steel wool and then treated again with Golvolja. Wait about 15 minutes, and then polish with a nylon rag.

**As a primer before a floor is varnished with Parkettlack:** Apply a thin coat of Golvolja, board by board, and then let the wood absorb the oil. Wipe the surface afterwards. Make a test on a loose board before treating the entire floor. Golvolja can also be tinted with oil-based artists' colours (Beckers Normalfärg). The drying time is about 24 hours when Golvolja is used to prime hardwood flooring before varnishing with Parkettlack.

**Cleaning:** Tools are cleaned with white spirit or Beckers Penseltvätt paintbrush cleaner. Do not pour liquid waste down the drain take it to a local environmental station for disposal. Hand in empty cans for recycling at an authorized facility.

**CAUTION:** Used rags and similar cloths are to be soaked in water or burned since there is a risk that they will self-ignite.

Make sure that the oil does not penetrate underlying insulation material.

Do not use Golvolja close to an open fire or hot objects.