

Beckers



Decor Metall

Decor Metall is a waterborne acrylic enamel paint for decorative painting indoors on small wall surfaces, small ceiling areas, columns, ornaments and knick-knacks, furniture and similar objects. Decor Metall creates a beautiful metallic finish.

Decor Metall is normally used as primer and finish coat. The paint does not contain white spirit or other strong solvents.

Depending on the application method, Decor Metall can be used to create many different types of decorative effects.



TECHNICAL DATA

BINDER	Acrylic.
THINNING	Water.
COVERAGE	1 litre is enough to cover approximately 8 m ² .
TOOLS	Use a paintbrush or roller.
CLEANING OF TOOLS	Use water.
DRYING TIME	Tack-free after about 12 hours at the earliest at a temperature of +23°C and 50% relative humidity.
GLOSS	Semi-glossy.
COLOUR RANGE	Gold and silver.
FLAMMABILITY	Non-flammable.
STORAGE	Store above freezing.

Decor Metall

INSTRUCTIONS

PAINTED/FINISHED SURFACES: Wash the surface with Beckers Målartvätt liquid degreaser and cleaner and rinse thoroughly afterwards. Sand shiny areas and spots until they are dull. Scrape with a brush to remove all loose paint. Spackle all uneven areas with Breplasta Spackel or Snickerispackel. Prime with one coat of Decor Metall. Apply the second coat the following day.

WALLS: Decor Metall is normally applied directly onto the wall surface. Use a roller with a fine nap, such as a Finlon or Filtrulle felt roller. If the wall is covered with several types of material, such as gypsum, spackle or wallpaper, the wall should first be primed with a wall primer or Decor Lasyrgrund primer for an even result and finish.

NEW UNFINISHED WOOD AND WOOD THAT HAS BEEN SCRAPED BARE: Paint knots with one coat of Kvistlack. If you have to spackle any areas, wait until after you have applied the first coat of Decor Metall. Spackled areas are preferably painted with an extra coat. Sand the spackled surface smooth with fine sandpaper.

FACTORY-FINISHED (HARD ENAMELED) SURFACES: Sand the surface thoroughly with fine sandpaper and apply at least two coats of Decor Metall.

PAINTING

Apply at least two coats of Decor Metall, waiting to apply the second coat until the following day. Stir the paint thoroughly from the bottom of the can. Decor Metall can be applied with a paintbrush or roller. You can create different effects, depending on the type of painting technique you use. See the instruction sheet for Decor Metall and the Dimension brochure for further information, or contact your local Beckers dealer.

CLEANING: Wipe away excessive paint on tools before cleaning them in water. This will reduce the load on your local sewage treatment plant. Seal open cans tightly. Liquid waste and wash water should be handed in for proper treatment at your local environmental station. Empty cans can be handed in at your authorized recycling centre.

Do not paint surfaces that are colder than +8°C.