

# Beckers



## Decor Latextempera

Decor Latextempera is a flat, water-based latex paint that contains no solvent or ammonia additives. The product is used to paint interior walls and ceilings when a classic tempera finish is desired. Decor Latextempera is used mainly to paint new unpainted surfaces, or to paint over surfaces covered with latex paint.

Decor Latextempera is used mainly to paint new unpainted surfaces, or to paint over surfaces covered with latex paint.

Decor Latextempera contains no solvents, ammonia or coalescing agents, it is very suitable for day-care centres, pre-schools, hospitals and other sensitive environments that must be non-allergenic. Decor Latextempera is also a good choice for working environments since it is virtually odourless during painting and drying. The paint has an even grain, dries quickly and can be painted over after about 3 hours. Decor Latextempera does not yellow with age. It creates a durable and washable finish that is also easy to touch up when repairs are needed. Decor Latextempera has a very long can storage life.



### TECHNICAL DATA

<b>BINDER</b>	Co-polymer latex.
<b>SOLVENT</b>	Water.
<b>THINNING</b>	Water.
<b>COVERAGE</b>	6-8 m <sup>2</sup>
<b>TOOLS</b>	Use a paintbrush, roller or spray gun.
<b>CLEANING OF TOOLS</b>	Use water.
<b>DRYING TIME</b>	Tack-free after 30 minutes, completely dry after 3 hours.
<b>GLOSS</b>	Flat, about 3 gloss units.
<b>COLOUR RANGE</b>	Can be tinted in the Beckers Colour System.
<b>NON-VOLATILE MATTER</b>	Approx 35% volume.
<b>FLAMMABILITY</b>	Non-flammable.
<b>STORAGE</b>	Store above freezing.

# Decor Latextempera

## INSTRUCTIONS NEW UNPAINTED SURFACES

### Prepering the surface

**Plastered surfaces, stucco, concrete, fibreboard, particleboard, plasterboard and woven fabric wall coverings:** Brush away any loose dirt, particles and dust. Prime with Beckers' Scotte Grund primer.

**Repairing, filling and levelling with spackle:** Use Beckers' spackling compounds, either Breplasta or Beckers Väggs-packel wall spackle.

**Finish coat:** Use Decor Latextempera for the finish coat.

## PREVIOUSLY PAINTED SURFACES

**Surfaces painted with latex, alkyd and oil paints:** Wash the surface clean with Beckers Tar-väck Målartvätt degreaser/cleaner or a similar cleaner. Rinse thoroughly with water. Between coats, dull any shiny spots by rubbing with medium-grade sandpaper to provide the best possible surface for the paint to adhere to. Surfaces painted with alkyd and oil paints are to be primed first with Scotte Grund primer.

**Surfaces painted with distemper:** Wash away the distemper with water. Seal the surface with Beckers' Scotte Patentfärg paint, then prime with Scotte Grund.

**Limed surfaces:** Scrape and brush the surface until it is sound. Dust or rinse with water. Seal the surface with Beckers' Scotte Patentfärg paint, then prime with Scotte Grund.

**Repairing, filling and levelling with spackle:** Use Beckers' spackling compounds, either Breplasta or Beckers Väggs-packel wall spackle.

## FINISH COAT

Use Decor Latextempera for the finish coat.

**Thinning:** The paint is usually not thinned. If necessary, thin with water.

**Application:** Roller or sprayer. Strain the paint before using it in a high-pressure sprayer.

**Cleaning:** Tools are cleaned with water immediately after use.

**Caution:** Do not paint surfaces with a temperature below +5 degrees C.